

Love Life Love Color

WATERPROOF LVP FLOORING

Heemo Collection – Wood Grains Embossed



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating



Strip Natural



Hazelnut



Sahara



Pecan



Himalaya



Caramel



Titanium



Dark Chip



Cherry Oak

WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating



Almond



Caramel Oak



Neoland



Asphalt



Iced Charclonny

WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Strip Natural
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Hazelnut
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Sahara
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Pecan
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Himalaya
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Caramel
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Titanium
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Dark Chip
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Cherry Oak
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Almond
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Caramel Oak
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Neoland
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Asphalt
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs



WATERPROOF LVP FLOORING

Heemo Collection

5.0 mm - 20 mil - Unilin Click - Deep Embossed - UV coating

Color name:	Iced Charclonny
Construction:	Rigid Core
Overall Thickness:	5.0 mm
Wear Layer:	20 Mil
Underlayment :	IXPE 15x 1.0mm
Size:	7"x48"
SqFt Per Carton:	23.896 sqf
SqFt Per Pallet:	1194.80 sqf
SqFt Per Truckload:	23896.00 sqf
Truckload weight:	50.000.00 lbs

